



**RELEASED**  
2014-08-27

- NOTES:**
- 1) MATERIAL: 6061-T6/T6510/T62 ALUMINUM ROUND BAR PER QQ-A-225/8 OR AMS-QQ-A-225/8 (OR AMS 4117/4128/4115/4116) OR QQ-A-200/8 OR AMS-QQ-A-200/8 (OR AMS 4160) OR ASTM B211 OR ASTM B221 (REF DART SPEC M6061T6R0.750)
  - 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
  - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
  - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
  - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
  - 6) IDENTIFICATION: BAG AND TAG WITH DART P/N "D2022-101" OR "D2022-103" PER QSI 044 6.7
  - 7) WEIGHT: 0.01 lbs

B	RE-FORMAT DRAWING	DB	14.03.12
A	NEW ISSUE	JB	90.08.15
REV.	DESCRIPTION	BY	DATE
DESIGN	DB	<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA	
DRAWN	DB		
CHECKED	AP	DRAWING NO.	REV. B
MFG. APPR.	JLM	<b>D2022</b>	SHEET 1 OF 1
APPROVED	MP	TITLE	SCALE
DE APPR.	DS	<b>SPACER</b>	NTS
DATE	14.03.12	COPYRIGHT © 1990 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	